

HV Switchgear Lubricant, 10 Wt Oz (Discontinued)

No. 02060 | Item# 1003187 | Case# 1003186

Product Description A one-step lubricant and corrosion inhibitor for metering,

distribution and substation class switchgear contacts. It penetrates to coat contacts and provides corrosion

protection on switchgear mechanisms.

Applications Recommended for use on metering, distribution and

substation class switchgear contacts, including URD and

OVH applications.

Product Discontinued

Unit Package Description 16 Ounce Aerosol

Brand CRC

Generic Description 1 Utility Lubricant

Use Restrictions Contains HCFC(225), which has use restrictions and may

only be sold to professional users for applications

consistent with the regulation.

Net Fill 10 Wt Oz

UPC Code 078254020600

Unit Dimensions 7.75H x 2.63W x 2.63D in

Units Per Case 12

Case Dimensions 8.1H x 8.3W x 11.1D in

Cases Per Pallet 133
Case Weight 11 lbs

I 2 of 5 Code 30078254020601

Appearance Translucent White Liquid

Base Type Silicone
Flash point (F) None
Flash point (C) None
Flammability Class - CPSC None
Spec Gravity Concentrate 1.45

Plastic Safe Safe on Most Plastics (Test small area)

Film Type Grease

Film Thickness Not Determined

Last revised: 5/17/2019

Page 1 of 2





Evaporation Rate Fast

Dielectric Strength 28,000 Volts
Working Temp (F) -70 to 400°F

Working Temp (C) -56.7 to 204.4°C

Propellant HFC-134a

Aerosol Flammability Level | |

DOT Proper Shipping Name Aerosols, Non-Flammable, Limited Quantity

VOC % (Consumer Product 6

def)

Product

Discontinued

VOC g/L (Consumer 87

Product def)

VOC lbs/gal (Consumer 0.72

Prod def)

VOC Category Not Regulated (Single Purpose Lubricant)

Removal (How To) Remove with chlorinated solvents.

Last revised: 5/17/2019

Page 2 of 2

