



## Product Discontinued

### HV Switchgear Lubricant, 10 Wt Oz (Discontinued )

No. 02060 | Item# 1003187 | Case# 1003186

Product Description	A one-step lubricant and corrosion inhibitor for metering, distribution and substation class switchgear contacts. It penetrates to coat contacts and provides corrosion protection on switchgear mechanisms.
Applications	Recommended for use on metering, distribution and substation class switchgear contacts, including URD and OVH applications.
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	Utility Lubricant
Use Restrictions	Contains HCFC(225), which has use restrictions and may only be sold to professional users for applications consistent with the regulation.
Net Fill	10 Wt Oz
UPC Code	078254020600
Unit Dimensions	7.75H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	8.1H x 8.3W x 11.1D in
Cases Per Pallet	133
Case Weight	11 lbs
I 2 of 5 Code	30078254020601
Appearance	Translucent White Liquid
Base Type	Silicone
Flash point (F)	None
Flash point (C)	None
Flammability Class - CPSC	None
Spec Gravity Concentrate	1.45
Plastic Safe	Safe on Most Plastics (Test small area)
Film Type	Grease
Film Thickness	Not Determined

Last revised: 5/17/2019

Page 1 of 2



**Chemical Solutions to Keep You Moving™**

f t+ d+ in+ • 800-272-8963 • [crcindustries.com](http://crcindustries.com)



**Product  
Discontinued**

Evaporation Rate	Fast
Dielectric Strength	28,000 Volts
Working Temp (F)	-70 to 400°F
Working Temp (C)	-56.7 to 204.4°C
Propellant	HFC-134a
Aerosol Flammability Level	I
DOT Proper Shipping Name	Aerosols, Non-Flammable, Limited Quantity
VOC % (Consumer Product def)	6
VOC g/L (Consumer Product def)	87
VOC lbs/gal (Consumer Prod def)	0.72
VOC Category	Not Regulated (Single Purpose Lubricant)
Removal (How To)	Remove with chlorinated solvents.

Last revised: 5/17/2019  
Page 2 of 2