



Dielectric Grease, 3.3 Wt Oz

No. 02085 | Item# 1003199 | Case# 1003198

Product Description Non-curing silicone compound used for electrical sealing,

lubricating, protecting and insulating. Waterproofs electrical connections and components. Improves electrical performance in adverse weather conditions.

Applications Electrical panels, outdoor lighting, scoreboards, traffic

lights, high voltage poles, transformers, disconnects, switching mechanisms, electrical contacts, spark plugs, battery terminals, fasteners, o-rings, rubber and plastic

parts.

Unit Package Description 6 Ounce Pressurized Tube with Select-a-BEAD® Nozzle

Brand CRC

Generic Description 1 Non-Curing Silicone Compound for Sealing, Lubricating,

Protecting, And Insulating Electrical Components

Net Fill 3.3 Wt Oz

UPC Code 078254020853

Unit Dimensions 8.75H x 2.25W x 2.25D in

Units Per Case 12

Case Dimensions 8.75H x 7.37W x 7.37D in

Cases Per Pallet 120
Case Weight 6 lbs

I 2 of 5 Code 30078254020854 Appearance Opaque White Gel

Base Type Silicone
Flash point (F) >572°F
Flash point (C) >300°C
Flammability Class - CPSC None
Spec Gravity Concentrate 0.97

Plastic Safe Safe on Most Plastics (Test small area)

Film Type Non-Curing Silicone Paste

Dielectric Strength >450 Volts/Mil

NLGI Grade 2

Last revised: 9/5/2019

Page 1 of 2







Working Temp (F) -70 to 400°F Working Temp (C) -56.7 to 204.4°C

Propellant Nitrogen

NSF Category Code H1

NSF Number 151609

Meets requirements of SAE-AS-8660

Military Specification Number

Federal Specification FDA-CFR-21-178.3570

Number

Aerosol Flammability Level

DOT Proper Shipping Name Aerosols, Non-Flammable, Limited Quantity

VOC % (Consumer Product

def)

VOC g/L (Consumer < 0.01

Product def)

VOC lbs/gal (Consumer < 0.1

Prod def)

VOC Category Not Regulated

Removal (How To) Remove with petroleum distillates and chlorinated

solvents.

Last revised: 9/5/2019

Page 2 of 2

