



Electrical Silicone Lubricant, 5 Gal

No. 02096 | Item# 1003202

Product Description Specially formulated to lubricate, waterproof and protect

electrical components. Meets FDA Regulation CFR 21-178.3570 for incidental food contact. NSF H1 Registered.

Applications Helps prevent corrosion to electrical equipment located in

wet or harsh environments.

Unit Package Description 5 Gallon Pail

Brand CRC

Generic Description 1 Dry Film Silicone Lubricant

Net Fill 5 Gal

UPC Code 078254020969

Unit Dimensions 13.75H x 11.25W x 11.25D in

Units Per Case 1

Case Dimensions 13.8H x 11.3W x 11.3D in

Cases Per Pallet 24
Case Weight 32 lbs

Appearance Clear Water-White Liquid

Base Type Silicone
Flash point (F) <0°F
Flash point (C) <-18°C

Flammability Class - CPSC Extremely Flammable

Spec Gravity Concentrate 0.6694

Plastic Safe May Harm Sensitive Plastics
Film Type Dry, Clear, Non-Hardening

Evaporation Rate Fast

Dielectric Strength 350 Volts/Mil
Working Temp (F) -40 to 400°F
Working Temp (C) -40 to 204.4°C

Propellant None NSF Category Code H1

Last revised: 9/5/2019

Page 1 of 2







NSF Number 111206

DOT Proper Shipping Name Hexane Mixture (Marine Pollutant)

VOC % (Consumer Product 97

def)

VOC g/L (Consumer 649.3

Product def)

VOC lbs/gal (Consumer 5.4

Prod def)

VOC Category Not Regulated (Single Purpose Lubricant)

Removal (How To) Remove with soap & water, CRC HydroForce® All

Purpose, etc. and elbow power (scrubbing).

