



Electrical Silicone Lubricant, 55 Gal

No. 02097 | Item# 1003203

Product Description	Specially formulated to lubricate, waterproof and protect electrical components. Meets FDA Regulation CFR 21-178.3570 for incidental food contact. NSF H1 Registered.
Applications	Helps prevent corrosion to electrical equipment located in wet or harsh environments.
Unit Package Description	55 Gallon Drum
Brand	CRC
Generic Description 1	Dry Film Silicone Lubricant
Net Fill	55 Gal
UPC Code	078254020976
Unit Dimensions	35H x 24.5W x 24.5D in
Units Per Case	1
Case Dimensions	35H x 24.5W x 24.5D in
Cases Per Pallet	4
Case Weight	346 lbs
Appearance	Clear Water-White Liquid
Base Type	Silicone
Flash point (F)	<0°F
Flash point (C)	<-18°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.6694
Plastic Safe	May Harm Sensitive Plastics
Film Type	Dry, Clear, Non-Hardening
Evaporation Rate	Fast
Dielectric Strength	350 Volts/Mil
Working Temp (F)	-40 to 400°F
Working Temp (C)	-40 to 204.4°C
Propellant	None
NSF Category Code	H1

Last revised: 9/5/2019

Page 1 of 2



Chemical Solutions to Keep You Moving™

f t+ d+ in m • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



NSF Number	111206
DOT Proper Shipping Name	Hexane Mixture (Marine Pollutant)
VOC % (Consumer Product def)	97
VOC g/L (Consumer Product def)	649.3
VOC lbs/gal (Consumer Prod def)	5.4
VOC Category	Not Regulated (Single Purpose Lubricant)
Removal (How To)	Remove with soap & water, CRC HydroForce® All Purpose, etc. and elbow power (scrubbing).