



## Technical Grade 3-36® Multi-Purpose Precision Lubricant, 11 Wt Oz

No. 03003 | Item# 1003251 | Case# 1003250

### Product Description

Plastic safe lubricant, penetrant and corrosion inhibitor that helps prevent electrical malfunctions caused by water penetration, humidity or condensation. Cleans, lubricates, penetrates and loosens corrosion.

### Applications

Electrical connectors, relays, circuit breakers, transformers, switchgear, motors, hinges, generators, controls, instruments, communication assemblies, electronics, alarm systems, starters, hand tools, modern plastics and insulators.

### Unit Package Description

16 Ounce Aerosol

### Brand

CRC

### Generic Description 1

Plastic Safe, Multi-Purpose Precision Lubricant

### Net Fill

11 Wt Oz

### UPC Code

078254030036

### Unit Dimensions

7.75H x 2.63W x 2.63D in

### Units Per Case

12

### Case Dimensions

8.1H x 8.3W x 11.1D in

### Cases Per Pallet

133

### Case Weight

12 lbs

### I 2 of 5 Code

30078254030037

### Appearance

Amber Liquid

### Base Type

Petroleum Distillate

### Flash point (F)

200°F

### Flash point (C)

93°C

### Flammability Class - CPSC

Flammable

### Spec Gravity Concentrate

0.82

### Plastic Safe

Yes

### Film Type

Thin, Non-Drying

### Film Thickness

0.025 to 0.075 Mils

Last revised: 3/19/2021

Page 1 of 2



**Chemical Solutions to Keep You Moving™**

f t y o i n • 800-272-8963 • [crcindustries.com](http://crcindustries.com)

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



Evaporation Rate	Slow
Dielectric Strength	51,300 Volts
Working Temp (F)	Max 250°F
Working Temp (C)	Max 121.1°C
Propellant	Carbon Dioxide
NSF Category Code	H2
NSF Number	017424
Military Specification Number	Not Determined
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Multi-Purpose Lubricant
Removal (How To)	Remove with Petroleum Distillates.

