



3-36® Multi-Purpose Lubricant & Corrosion Inhibitor, 55 Gal No. 03011 | Item# 1003262

Product Description A versatile petroleum based compound that forms a clear,

thin film that lubricates and protects against wear and corrosion. Multi-purpose product lubricates, protects,

displaces moisture, and cleans.

Applications Tubing, castings, gears, weld rod, wire, fixtures, dies, jigs,

shim stock, chucks, drill rod, heat treated parts, machined

surfaces, finished welds, aluminum extrusions, air

actuated tools, conveyors, frozen joints, locks, hoists, etc.

Unit Package Description 55 Gallon Drum

Brand CRC

Generic Description 1 Multi-Purpose Precision Lubricant & Corrosion Inhibitor

Net Fill 55 Gal

UPC Code 078254030111

Unit Dimensions 35H x 24.5W x 24.5D in

Units Per Case 1

Case Dimensions 35H x 24.5W x 24.5D in

Cases Per Pallet 4

Case Weight 430 lbs

Appearance Clear Blue-Green Liquid

Base Type Petroleum

Flash point (F) 192°F
Flash point (C) 89°C
Flammability Class - CPSC None
Spec Gravity Concentrate 0.83

Film Type Non-Drying

Film Thickness 0.025 to 0.075 Mils

No

Evaporation Rate Slow

Plastic Safe

Dielectric Strength 38,800 Volts Working Temp (F) -50 to 250°F

Last revised: 3/31/2020

Page 1 of 2







Working Temp (C) -45.6 to 121.1°C

Propellant None NSF Category Code H2

NSF Number 017429

Federal Specification V-V-P-216,O-W-1284

Number

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product)

def)

VOC g/L (Consumer

Product def)

0

VOC lbs/gal (Consumer

Prod def)

0

VOC Category Multi-Purpose Lubricant

Removal (How To) Remove with petroleum products, mineral spirits, or

contact cleaner.

