



3-36® Multi-Purpose Lubricant & Corrosion Inhibitor, 55 Gal No. 03011 | Item# 1003262

| | |
|---------------------------|---|
| Product Description | A versatile petroleum based compound that forms a clear, thin film that lubricates and protects against wear and corrosion. Multi-purpose product lubricates, protects, displaces moisture, and cleans. |
| Applications | Tubing, castings, gears, weld rod, wire, fixtures, dies, jigs, shim stock, chucks, drill rod, heat treated parts, machined surfaces, finished welds, aluminum extrusions, air actuated tools, conveyors, frozen joints, locks, hoists, etc. |
| Unit Package Description | 55 Gallon Drum |
| Brand | CRC |
| Generic Description 1 | Multi-Purpose Precision Lubricant & Corrosion Inhibitor |
| Net Fill | 55 Gal |
| UPC Code | 078254030111 |
| Unit Dimensions | 35H x 24.5W x 24.5D in |
| Units Per Case | 1 |
| Case Dimensions | 35H x 24.5W x 24.5D in |
| Cases Per Pallet | 4 |
| Case Weight | 430 lbs |
| Appearance | Clear Blue-Green Liquid |
| Base Type | Petroleum |
| Flash point (F) | 192°F |
| Flash point (C) | 89°C |
| Flammability Class - CPSC | None |
| Spec Gravity Concentrate | 0.83 |
| Plastic Safe | No |
| Film Type | Non-Drying |
| Film Thickness | 0.025 to 0.075 Mils |
| Evaporation Rate | Slow |
| Dielectric Strength | 38,800 Volts |
| Working Temp (F) | -50 to 250°F |

Last revised: 3/31/2020
Page 1 of 2



Chemical Solutions to Keep You Moving™
f t+ in • 800-272-8963 • crcindustries.com



| | |
|---------------------------------|--|
| Working Temp (C) | -45.6 to 121.1°C |
| Propellant | None |
| NSF Category Code | H2 |
| NSF Number | 017429 |
| Federal Specification Number | V-V-P-216,O-W-1284 |
| DOT Proper Shipping Name | Not Regulated |
| VOC % (Consumer Product def) | 0 |
| VOC g/L (Consumer Product def) | 0 |
| VOC lbs/gal (Consumer Prod def) | 0 |
| VOC Category | Multi-Purpose Lubricant |
| Removal (How To) | Remove with petroleum products, mineral spirits, or contact cleaner. |