



Roll-up Door Lubricant, 11 Wt Oz
 No. 03029 | Item# 1003283 | Case# 1003282

Product Description	A superior lubricant that prevents friction and wear. Its unique viscosity allows it to cover more surface area and penetrate deep into the surface of all metal components found on roll-up and overhead doors.
Applications	Recommended for use on all roll-up and overhead door assemblies including dock doors, trailer doors as well as side panel doors on beverage trucks. Use to lubricate and protect door hinges, pins, cable, chains, bearings, rollers, and tracks.
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	Multi-Purpose Precision Lubricant
Net Fill	11 Wt Oz
UPC Code	078254030296
Unit Dimensions	7.75H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	8.1H x 8.3W x 11.1D in
Cases Per Pallet	133
Case Weight	11 lbs
1 2 of 5 Code	30078254030297
Appearance	Clear Blue-Green Liquid
Base Type	Petroleum
Flash point (F)	192°F
Flash point (C)	89°C
Flammability Class - CPSC	Flammable
Spec Gravity Concentrate	0.827
Plastic Safe	No
Film Type	Non-Drying
Film Thickness	0.025 to 0.075 MILS
Evaporation Rate	Slow

Last revised: 7/30/2019
 Page 1 of 2





Dielectric Strength	38,800 Volts
Working Temp (F)	-50 to 250°F
Working Temp (C)	-45.6 to 121.1°C
Propellant	Carbon Dioxide
NSF Category Code	H2
NSF Number	143101
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Multi-Purpose Lubricant
Removal (How To)	Remove with petroleum products, mineral spirits, or contact cleaner.

Last revised: 7/30/2019
Page 2 of 2



Chemical Solutions to Keep You Moving™
f t y d in • 800-272-8963 • crcindustries.com