



Roll-up Door Lubricant, 11 Wt Oz

No. 03029 | Item# 1003283 | Case# 1003282

Product Description

A superior lubricant that prevents friction and wear. Its unique viscosity allows it to cover more surface area and penetrate deep into the surface of all metal components found on roll-up and overhead doors.

Applications

Recommended for use on all roll-up and overhead door assemblies including dock doors, trailer doors as well as side panel doors on beverage trucks. Use to lubricate and protect door hinges, pins, cable, chains, bearings, rollers, and tracks.

Unit Package Description

16 Ounce Aerosol

Brand

CRC

Generic Description 1

Multi-Purpose Precision Lubricant

Net Fill

11 Wt Oz

UPC Code

078254030296

Unit Dimensions

7.75H x 2.63W x 2.63D in

Units Per Case

12

Case Dimensions

8.1H x 8.3W x 11.1D in

Cases Per Pallet

133

Case Weight

11 lbs

I 2 of 5 Code

30078254030297

Appearance

Clear Blue-Green Liquid

Base Type

Petroleum

Flash point (F)

192°F

Flash point (C)

89°C

Flammability Class - CPSC

Flammable

Spec Gravity Concentrate

0.827

Plastic Safe

No

Film Type

Non-Drying

Film Thickness

0.025 to 0.075 Mills

Evaporation Rate

Slow

Last revised: 7/30/2019

Page 1 of 2



Chemical Solutions to Keep You Moving™
f t y i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



Dielectric Strength	38,800 Volts
Working Temp (F)	-50 to 250°F
Working Temp (C)	-45.6 to 121.1°C
Propellant	Carbon Dioxide
NSF Category Code	H2
NSF Number	143101
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Multi-Purpose Lubricant
Removal (How To)	Remove with petroleum products, mineral spirits, or contact cleaner.

