



**Extreme Duty Silicone, 10 Wt Oz**  
 No. 03030 | Item# 1003285 | Case# 1003284

Product Description	Silicone fluid with superior lubrication and temperature viscosity characteristics. Use on all metallic and non-metallic surfaces. Reduces friction and galling even on metal-to-metal contact areas.
Applications	Plant conveyors, guides and rails, mold release agents, vending machines, electric motors and rollers and sliding mechanisms
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	Premium Grade Silicone Lubricant
Net Fill	10 Wt Oz
UPC Code	078254030302
Unit Dimensions	7.75H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	8.1H x 8.3W x 11.1D in
Cases Per Pallet	133
Case Weight	11 lbs
I 2 of 5 Code	30078254030303
Appearance	Clear Colorless Liquid
Base Type	Silicone
Flash point (F)	<0°F
Flash point (C)	<-18°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.6699
Plastic Safe	Safe on Most Plastics (Test small area)
Film Type	Dry Film
Film Thickness	Not Determined
Evaporation Rate	Fast
Dielectric Strength	Not Determined
Working Temp (F)	-100 to 450°F

Last revised: 9/5/2019  
 Page 1 of 2



Working Temp (C)	204.4°C
Propellant	HFC-152a
NSF Category Code	H2
NSF Number	116808
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	60
VOC g/L (Consumer Product def)	400.2
VOC lbs/gal (Consumer Prod def)	3.34
VOC Category	Silicone Based Multi-Purpose Lubricant
Removal (How To)	Mineral Spirits