



**Product
Discontinued**

Quick Dry Moly Lube, 14 Wt Oz (Discontinued)

No. 03043 | Item# 1003300

Product Description	Lowers friction, prevents galling and helps to reduce torque and energy consumption. High anti-friction and anti-seizure properties. Fast drying film resists dirt and dust build-up.
Applications	Gaskets, transfer belts, conveyor belts, motors, plant machinery and handling equipment, rubber moldings, high temperature, low load, or high rpm slides, rollers, wheels, gears, chains & hoists
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	Dry Film Lubricant
Net Fill	14 Wt Oz
UPC Code	078254030432
Unit Dimensions	7.75H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	8.1H x 8.3W x 11.1D in
Cases Per Pallet	152
Case Weight	11 lbs
I 2 of 5 Code	30078254030433
Appearance	Black Liquid
Base Type	Organic Solvents
Flash point (F)	54°F
Flash point (C)	12°C
Flammability Class - CPSC	Flammable
Spec Gravity Concentrate	1.32
Plastic Safe	No
Film Type	Dry
Evaporation Rate	Fast
Working Temp (F)	650°F
Working Temp (C)	343.3°C

Last revised: 10/21/2019
Page 1 of 2





**Product
Discontinued**

Propellant	Hydrocarbon
Aerosol Flammability Level	II
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	27
VOC g/L (Consumer Product def)	356.4
VOC lbs/gal (Consumer Prod def)	2.97
VOC Category	Dry Film Lubricant
Removal (How To)	Remove with petroleum solvents.