

Heavy Duty Clear Penetrating Grease, 13 Wt Oz

No. 03056 | Item# 1003316 | Case# 1003315

Product Description

A high tack, clear lubricating gel which provides lubrication at temperatures from -30°F to 500°F. High adhesive strength ensures the product will resist throw off and water wash-out.

Applications

Gears, sprockets, hinges, chains, cable, wire rope, slides, valves, pistons, rings, seals, bearings, sleeves, cams, and bushings

Unit Package Description

20 Ounce Aerosol

Brand

CRC

Generic Description 1

Penetrating Grease

Net Fill

13 Wt Oz

UPC Code

078254030562

Unit Dimensions

9.25H x 2.63W x 2.63D in

Units Per Case

12

Case Dimensions

9.7H x 8.3W x 11.1D in

Cases Per Pallet

114

Case Weight

11 lbs

I 2 of 5 Code

30078254030563

Appearance

Clear Liquid

Base Type

Petroleum

Flash point (F)

<20°F

Flash point (C)

<-7°C

Flammability Class - CPSC

Extremely Flammable

Spec Gravity Concentrate

0.8

Plastic Safe

No

Film Type

Clear Oily

Evaporation Rate

Fast

Dielectric Strength

Not Determined

NLGI Grade

Not Determined

Working Temp (F)

-30 to 500°F

Last revised: 11/14/2019

Page 1 of 2




Chemical Solutions to Keep You Moving™

f t y o i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



| | |
|---------------------------------|---------------------------------------|
| Working Temp (C) | -34.4 to 260°C |
| Propellant | Hydrocarbon |
| NSF Category Code | H2 |
| NSF Number | 145908 |
| Aerosol Flammability Level | III |
| DOT Proper Shipping Name | Aerosols, Flammable, Limited Quantity |
| VOC % (Consumer Product def) | 45 |
| VOC g/L (Consumer Product def) | 360 |
| VOC lbs/gal (Consumer Prod def) | 3.0 |
| VOC Category | Penetrant |
| Restricted from Sale In: | CA |
| Removal (How To) | Remove with Petroleum Distillates. |

