



## CRC Red Grease, 1x11OZ

No. 03079 | Item# 1003339 | Case# 1003338

Product Description	Heavy-duty lubricant that withstands high temperature and high pressure. Red color allows for easy visual inspection of film coverage.
Applications	Bearings, pillow blocks, U-joints, heavy equip., 5th wheels, electrical motor shafts, roller chain, pulley, hinges, latches, overhead door track, open gears, chains, cables, slide conveyors, guide rails, cams, pistons, machinery, tools, & equipment.
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	Aluminum Complex Red Aerosol Grease
Net Fill	11 Wt Oz
UPC Code	078254030791
Unit Dimensions	7.75H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	8.69H x 8.44W x 11.31D in
Cases Per Pallet	133
Case Weight	12 lbs
I 2 of 5 Code	30078254030792
Appearance	Red Viscous Grease
Base Type	Aluminum Complex
Flash point (F)	<23°F
Flash point (C)	<-5°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.72
Plastic Safe	Yes
Film Type	Grease
Film Thickness	Not Determined
Evaporation Rate	Fast
Dielectric Strength	Not Determined

Last revised: 2/5/2020

Page 1 of 2



**Chemical Solutions to Keep You Moving™**

f t y o i n • 800-272-8963 • [crcindustries.com](http://crcindustries.com)

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



ISO Viscosity Grade	Not Determined
NLGI Grade	2
Working Temp (F)	-25 to 300°F
Working Temp (C)	Max 260°C
Propellant	Hydrocarbon
Military Specification Number	Not Determined
Federal Specification Number	Not Determined
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	24.9
VOC g/L (Consumer Product def)	196
VOC lbs/gal (Consumer Prod def)	1.63
VOC Category	Multi-Purpose Lubricant
Removal (How To)	Remove with Petroleum Distillates.