



CRC Red Grease, 1x11OZ

No. 03079 | Item# 1003339 | Case# 1003338

Product Description

Heavy-duty lubricant that withstands high temperature and high pressure. Red color allows for easy visual inspection of film coverage.

Applications

Bearings, pillow blocks, U-joints, heavy equip., 5th wheels, electrical motor shafts, roller chain, pulley, hinges, latches, overhead door track, open gears, chains, cables, slide conveyors, guide rails, cams, pistons, machinery, tools, & equipment.

Unit Package Description

16 Ounce Aerosol

Brand

CRC

Generic Description 1

Aluminum Complex Red Aerosol Grease

Net Fill

11 Wt Oz

UPC Code

078254030791

Unit Dimensions

7.75H x 2.63W x 2.63D in

Units Per Case

12

Case Dimensions

8.69H x 8.44W x 11.31D in

Cases Per Pallet

133

Case Weight

12 lbs

I 2 of 5 Code

30078254030792

Appearance

Red Viscous Grease

Base Type

Aluminum Complex

Flash point (F)

<23°F

Flash point (C)

<-5°C

Flammability Class - CPSC

Extremely Flammable

Spec Gravity Concentrate

0.72

Plastic Safe

Yes

Film Type

Grease

Film Thickness

Not Determined

Evaporation Rate

Fast

Dielectric Strength

Not Determined

Last revised: 2/5/2020

Page 1 of 2



Chemical Solutions to Keep You Moving™
f t y o i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



ISO Viscosity Grade	Not Determined
NLGI Grade	2
Working Temp (F)	-25 to 300°F
Working Temp (C)	Max 260°C
Propellant	Hydrocarbon
Military Specification Number	Not Determined
Federal Specification Number	Not Determined
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	24.9
VOC g/L (Consumer Product def)	196
VOC lbs/gal (Consumer Prod def)	1.63
VOC Category	Multi-Purpose Lubricant
Removal (How To)	Remove with Petroleum Distillates.

