



Dry Moly Lube, 11 Wt Oz

No. 03084 | Item# 1003351 | Case# 1003350

Product Description

Lowers friction, prevents galling and helps to reduce torque and energy consumption. High anti-friction and anti-seizure properties. Fast drying film resists dirt and dust build-up.

Applications

Gaskets, transfer belts, conveyor belts, motors, plant machinery and handling equipment, rubber moldings, high temperature, low load, or high rpm slides, rollers, wheels, gears, chains & hoists

Unit Package Description

16 Ounce Aerosol

Brand

CRC

Generic Description 1

Dry Film Lubricant

Net Fill

11 Wt Oz

UPC Code

078254030845

Unit Dimensions

7.75H x 2.63W x 2.63D in

Units Per Case

12

Case Dimensions

8.6H x 8.4W x 11.3D in

Cases Per Pallet

133

Case Weight

12 lbs

I 2 of 5 Code

30078254030846

Appearance

Dark Gray Viscous Liquid

Base Type

Molybdenum Disulfide

Flash point (F)

-20°F

Flash point (C)

-29°C

Flammability Class - CPSC

Extremely Flammable

Spec Gravity Concentrate

0.71

Plastic Safe

No

Film Type

Dry

Evaporation Rate

Fast

Working Temp (F)

650°F (Continuous) / 750°F (Intermittent)

Working Temp (C)

343.3°C (Continuous) 398.9°C (Intermittent)

Last revised: 9/11/2020

Page 1 of 2



Chemical Solutions to Keep You Moving™

f t i n • 800-272-8963 • crcindustries.com



Propellant	Hydrocarbon
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	61.8
VOC g/L (Consumer Product def)	438.78
VOC lbs/gal (Consumer Prod def)	3.66
VOC Category	Dry Film Lubricant
Removal (How To)	Remove with a heavy duty degreaser.