



Food Grade Dielectric Grease, 3.3 Wt Oz

No. 03085 | Item# 1003353 | Case# 1003352

Product Description Non-curing silicone compound used for electrical sealing,

lubricating, protecting and insulating. Waterproofs electrical connections and components. Improves electrical performance in adverse weather conditions.

Applications Gaskets, transfer belts, conveyor belts, motors, plant

machinery and handling equipment, rubber moldings, high temperature, low load, or high rpm slides, rollers, wheels,

gears, chains & hoists

Unit Package Description 6 Ounce Pressurized Tube with Select-a-BEAD® Nozzle

Brand CR0

Generic Description 1 Non Curing Silicone Lubricating Compound

Net Fill 3.3 Wt Oz

UPC Code 078254030852

Unit Dimensions 8.75H x 2.25W x 2.25D in

Units Per Case 12

Case Dimensions 8.75H x 7.37W x 7.37D in

Cases Per Pallet 120
Case Weight 6 lbs

I 2 of 5 Code 30078254030853 Appearance Opaque White Gel

Base Type Silicone
Flash point (F) >572°F
Flash point (C) >300°C
Flammability Class - CPSC None
Spec Gravity Concentrate 0.97

Plastic Safe Safe on Most Plastics (Test small area)

Film Type Non-Curing Silicone Paste

Dielectric Strength >450 Volts/Mil

NLGI Grade 2

Working Temp (F) -70 to 400°F

Last revised: 9/5/2019

Page 1 of 2







Working Temp (C) -56.7 to 204.4°C

Propellant Nitrogen

NSF Category Code H1

NSF Number 151608

Military Specification Meets requirements of SAE-AS-8660

Number

Federal Specification FDA-CFR-21-178.3570

Number

Aerosol Flammability Level | |

DOT Proper Shipping Name Aerosols, Non-Flammable, Limited Quantity

VOC % (Consumer Product <

def)

VOC g/L (Consumer <0.01

Product def)

VOC lbs/gal (Consumer < 0.1

Prod def)

VOC Category Not Regulated

Removal (How To) Remove with Petroleum Distillates.

Last revised: 9/5/2019

Page 2 of 2

