



Dry Graphite Lube, 10 Wt Oz

No. 03094 | Item# 1003362 | Case# 1003361

Product Description	Ideal where a dry lubricant is required or where petroleum products must be avoided. Resists dirt, dust and oil build-up. Wide effective temperature range up to 850°F constant.
Applications	Gaskets, transfer belts, conveyor belts, motors, plant machinery and handling equipment, rubber moldings, high temperature, low load, or high rpm slides, rollers, wheels, gears, chains & hoists
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	Dry Graphite Lube
Net Fill	10 Wt Oz
UPC Code	078254030944
Unit Dimensions	7.75H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	8.69H x 8.44W x 11.31D in
Cases Per Pallet	133
Case Weight	12 lbs
I 2 of 5 Code	30078254030945
Appearance	Black Liquid
Base Type	Solvent
Flash point (F)	-20.2°F
Flash point (C)	-29°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.73
Plastic Safe	No
Film Type	Dry
Evaporation Rate	Moderate
Dielectric Strength	Conductive
Working Temp (F)	850°F (Constant) / 1000°F (Intermittent)

Last revised: 3/18/2021

Page 1 of 2



Chemical Solutions to Keep You Moving™

f t+ in • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



Working Temp (C)	454.4°C (Constant) 537.8°C (Intermittent)
Propellant	Hydrocarbon
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	Not regulated
VOC g/L (Consumer Product def)	Not regulated
VOC lbs/gal (Consumer Prod def)	Not regulated
VOC Category	Dry Film Lubricant
Restricted from Sale In:	No State Restrictions
Removal (How To)	Remove with petroleum solvents.

Last revised: 3/18/2021
Page 2 of 2