



**Ultra Lite 3-36® Ultra Thin Non Staining Lubricant, 1 Gal**  
 No. 03161 | Item# 1003429 | Case# 1003428

Product Description	Ultra-thin, non-staining lubricant that resists oil, dirt and dust build-up. Seals out moisture and prevents corrosion with protective film. Excellent for drying out electrical/electronic components.
Applications	Locks, latches, hinges, gauges, taps, dies, fixtures, fans, precision metal processing equipment, metal plating, coin mechanisms, solid work surfaces, clips, springs, control buttons, switches, bushings, window slides and rollers.
Unit Package Description	1 Gallon Bottle
Brand	CRC
Generic Description 1	Ultra Thin Non Staining Lubricant
Net Fill	1 Gal
UPC Code	078254031613
Unit Dimensions	10.25H x 5W x 6.13D in
Units Per Case	4
Case Dimensions	11.1H x 10.6W x 13.1D in
Cases Per Pallet	60
Case Weight	31 lbs
I 2 of 5 Code	30078254031614
Appearance	Amber Liquid
Base Type	Petroleum Solvent
Flash point (F)	172°F
Flash point (C)	78°C
Flammability Class - CPSC	Combustible
Spec Gravity Concentrate	0.8
Plastic Safe	No
Film Type	Ultra Thin and Dry
Film Thickness	0.05 Mil
Evaporation Rate	Slow
Dielectric Strength	37,600 Volts

Last revised: 9/5/2019  
 Page 1 of 2





Working Temp (F)	-40 to 300°F
Working Temp (C)	-40 to 148.9°C
Propellant	None
NSF Category Code	H2
NSF Number	136113
Military Specification Number	Meets requirements of Mil-PRF-16173E, Grade 3 (Corrosion test only)
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	45
VOC g/L (Consumer Product def)	361.5
VOC lbs/gal (Consumer Prod def)	3.0
VOC Category	Dry Film Lubricant
Removal (How To)	Remove with petroleum solvents, Stoddard solvent or mineral spirits.

Last revised: 9/5/2019  
Page 2 of 2