



Ultra Lite 3-36® Ultra Thin Non Staining Lubricant, 5 Gal No. 03162 | Item# 1003430

Product Description

Ultra-thin, non-staining lubricant that resists oil, dirt and dust build-up. Seals out moisture and prevents corrosion with protective film. Excellent for drying out electrical/electronic components.

Applications

Locks, latches, hinges, gauges, taps, dies, fixtures, fans, precision metal processing equipment, metal plating, coin mechanisms, solid work surfaces, clips, springs, control buttons, switches, bushings, window slides and rollers.

Unit Package Description

5 Gallon Pail

Brand

CRC

Generic Description 1

Ultra Thin Non Staining Lubricant

Net Fill

5 Gal

UPC Code

078254031620

Unit Dimensions

13.75H x 11.25W x 11.25D in

Units Per Case

1

Case Dimensions

13.8H x 11.3W x 11.3D in

Cases Per Pallet

24

Case Weight

35 lbs

Appearance

Amber Liquid

Base Type

Petroleum Solvent

Flash point (F)

172°F

Flash point (C)

78°C

Flammability Class - CPSC

Combustible

Spec Gravity Concentrate

0.8

Plastic Safe

No

Film Type

Ultra Thin and Dry

Film Thickness

0.05 Mils

Evaporation Rate

Slow

Dielectric Strength

37,600 Volts

Working Temp (F)

-40 to 300°F

Last revised: 1/2/2020

Page 1 of 2



Chemical Solutions to Keep You Moving™

f t y o i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



Working Temp (C)	-40 to 148.9°C
Propellant	None
NSF Category Code	H2
NSF Number	136113
Military Specification Number	Meets requirements of Mil-PRF-16173E, Grade 3 (Corrosion test only)
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	40.6
VOC g/L (Consumer Product def)	326.2
VOC lbs/gal (Consumer Prod def)	2.7
VOC Category	Dry Film Lubricant
Removal (How To)	Remove with petroleum solvents, Stoddard solvent or mineral spirits.

Last revised: 1/2/2020
Page 2 of 2



Chemical Solutions to Keep You Moving™
f t y o i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.