



Chute Lube™ Lubricant, 11 Wt Oz
 No. 03204 | Item# 1003459 | Case# 1003458

Product Description	An NSF registered H2, silicone lubricant for package handling applications. It eliminates the binding and sticking of packages and boxes, while protecting most surfaces.
Applications	Recommended to lubricate package handling equipment, such as chutes, slides, guides, and rails.
Unit Package Description	20 Ounce Aerosol
Brand	CRC
Generic Description 1	Silicone Lubricant
Net Fill	11 Wt Oz
UPC Code	078254032047
Unit Dimensions	9.25H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	9.7H x 8.3W x 11.1D in
Cases Per Pallet	114
Case Weight	12 lbs
I 2 of 5 Code	30078254032048
Appearance	Clear Light Yellow Liquid
Base Type	Silicone
Flash point (F)	<0°F
Flash point (C)	<-18°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.68
Plastic Safe	May Harm Sensitive Plastics
Film Type	Silicone
Evaporation Rate	Fast
Dielectric Strength	Not Determined
Working Temp (F)	-15 to 400°F
Working Temp (C)	-25 to 204°C

Last revised: 9/5/2019
 Page 1 of 2





Propellant	Hydrocarbon
NSF Category Code	H2
NSF Number	138031
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	94.97
VOC g/L (Consumer Product def)	646
VOC lbs/gal (Consumer Prod def)	5.4
VOC Category	Not Regulated (Single Purpose Lubricant)
Removal (How To)	Remove with Petroleum Distillates.

Last revised: 9/5/2019
Page 2 of 2