



Chute Lube™ Lubricant, 15 Fl Oz
 No. 03220 | Item# 1003464 | Case# 1003463

Product Description	An NSF registered H2, silicone lubricant for package handling applications. It eliminates the binding and sticking of packages and boxes, while protecting most surfaces.
Applications	Recommended to lubricate package handling equipment such as chutes, slides, guides and rails.
Unit Package Description	16 Ounce Bottle with Trigger
Brand	CRC
Generic Description 1	Silicone Lubricant
Net Fill	15 Fl Oz
UPC Code	078254032207
Unit Dimensions	9.38H x 2.75W x 3.75D in
Units Per Case	12
Case Dimensions	10.44H x 8.5W x 11.25D in
Cases Per Pallet	95
Case Weight	12 lbs
I 2 of 5 Code	30078254032208
Appearance	Clear Light Yellow Liquid
Base Type	Poly dimethylsiloxane
Flash point (F)	113°F
Flash point (C)	45°C
Flammability Class - CPSC	Combustible
Spec Gravity Concentrate	0.75
Plastic Safe	Safe on Most Plastics (Test small area)
Film Type	Wet
Film Thickness	Not Determined
Evaporation Rate	Slow
Dielectric Strength	Not Determined
Working Temp (F)	-40 to 400°F

Last revised: 7/30/2019
 Page 1 of 2





Working Temp (C)	-40 to 204.4°C
Propellant	None
NSF Category Code	H2
NSF Number	139430
DOT Proper Shipping Name	Not Regulated for ground shipping
VOC % (Consumer Product def)	90.4
VOC g/L (Consumer Product def)	684.8
VOC lbs/gal (Consumer Prod def)	5.7
VOC Category	Not Regulated (Single Purpose Lubricant)
Removal (How To)	Remove with Petroleum Distillates.

Last revised: 7/30/2019
Page 2 of 2