



Chute Lube™ Lubricant, 15 FI Oz No. 03220 | Item# 1003464 | Case# 1003463

Product Description An NSF registered H2, silicone lubricant for package

handling applications. It eliminates the binding and sticking of packages and boxes, while protecting most

surfaces.

Applications Recommended to lubricate package handling equipment

such as chutes, slides, guides and rails.

Unit Package Description 16 Ounce Bottle with Trigger

Brand CRC

Generic Description 1 Silicone Lubricant

Net Fill 15 Fl Oz

UPC Code 078254032207

Unit Dimensions 9.38H x 2.75W x 3.75D in

Units Per Case 12

Case Dimensions 10.44H x 8.5W x 11.25D in

Cases Per Pallet 95

Case Weight 12 lbs

1 2 of 5 Code 30078254032208

Appearance Clear Light Yellow Liquid
Base Type Poly dimthylsiloxane

Flash point (F) 113°F Flash point (C) 45°C

Flammability Class - CPSC Combustible

Spec Gravity Concentrate 0.75

Plastic Safe Safe on Most Plastics (Test small area)

Film Type Wet

Film Thickness Not Determined

Evaporation Rate Slow

Dielectric Strength Not Determined
Working Temp (F) -40 to 400°F

Last revised: 7/30/2019

Page 1 of 2







Working Temp (C) -40 to 204.4°C

Propellant None
NSF Category Code H2

NSF Number 139430

DOT Proper Shipping Name Not Regulated for ground shipping

VOC % (Consumer Product 90.4

def)

VOC g/L (Consumer 684.8

Product def)

VOC lbs/gal (Consumer 5.7

Prod def)

VOC Category Not Regulated (Single Purpose Lubricant)

Removal (How To) Remove with Petroleum Distillates.

