



**Chute Lube™ Lubricant, 5 Gal**  
 No. 03222 | Item# 1003466

Product Description	An NSF registered H2, silicone lubricant for package handling applications. It eliminates the binding and sticking of packages and boxes, while protecting most surfaces.
Applications	Recommended to lubricate package handling equipment such as chutes, slides, guides and rails.
Unit Package Description	5 Gallon Pail
Brand	CRC
Generic Description 1	Silicone Lubricant
Net Fill	5 Gal
UPC Code	078254032221
Unit Dimensions	13.75H x 11.25W x 11.25D in
Units Per Case	1
Case Dimensions	13.8H x 11.3W x 11.3D in
Cases Per Pallet	24
Case Weight	33 lbs
Appearance	Clear Light Yellow Liquid
Base Type	Poly dimethylsiloxane
Flash point (F)	113°F
Flash point (C)	45°C
Flammability Class - CPSC	Combustible
Spec Gravity Concentrate	0.75
Plastic Safe	Safe on Most Plastics (Test small area)
Film Type	Wet
Film Thickness	Not Determined
Evaporation Rate	Slow
Dielectric Strength	Not Determined
Working Temp (F)	-40 to 400°F
Working Temp (C)	-40 to 204.4°C

Last revised: 7/30/2019  
 Page 1 of 2





Propellant	None
NSF Category Code	H2
NSF Number	139430
DOT Proper Shipping Name	Not Regulated for ground shipping
VOC % (Consumer Product def)	90.4
VOC g/L (Consumer Product def)	684.8
VOC lbs/gal (Consumer Prod def)	5.7
VOC Category	Not Regulated (Single Purpose Lubricant)
Removal (How To)	Remove with Petroleum Distillates.

Last revised: 7/30/2019  
Page 2 of 2