



Chute Lube™ Lubricant, 55 Gal

No. 03223 | Item# 1003467

Product Description An NSF registered H2, silicone lubricant for package

handling applications. It eliminates the binding and sticking of packages and boxes, while protecting most

surfaces.

Applications Recommended to lubricate package handling equipment

such as chutes, slides, guides and rails.

Unit Package Description 55 Gallon Drum

Brand CRC

Generic Description 1 Silicone Lubricant

Net Fill 55 Gal

UPC Code 078254032238

Unit Dimensions 35H x 24.5W x 24.5D in

Units Per Case 1

Case Dimensions 35H x 24.5W x 24.5D in

Cases Per Pallet 4

Case Weight 430 lbs

Appearance Clear Light Yellow Liquid
Base Type Poly dimthylsiloxane

Flash point (F) 113°F Flash point (C) 45°C

Flammability Class - CPSC Combustible

Spec Gravity Concentrate 0.75

Plastic Safe Safe on Most Plastics (Test small area)

Film Type Wet

Film Thickness Not Determined

Evaporation Rate Slow

Dielectric Strength

Working Temp (F)

Working Temp (C)

Not Determined

-40 to 400°F

-40 to 204.4°C

Last revised: 7/30/2019

Page 1 of 2







Propellant None NSF Category Code H2

NSF Number 139430

DOT Proper Shipping Name Not Regulated for ground shipping

VOC % (Consumer Product 90.4

def)

VOC g/L (Consumer 684.8

Product def)

VOC lbs/gal (Consumer 5.7

Prod def)

VOC Category Not Regulated (Single Purpose Lubricant)

Removal (How To) Remove with Petroleum Distillates.

Last revised: 7/30/2019

Page 2 of 2

