



Chute Lube™ Lubricant, 55 Gal No. 03223 | Item# 1003467

Product Description	An NSF registered H2, silicone lubricant for package handling applications. It eliminates the binding and sticking of packages and boxes, while protecting most surfaces.
Applications	Recommended to lubricate package handling equipment such as chutes, slides, guides and rails.
Unit Package Description	55 Gallon Drum
Brand	CRC
Generic Description 1	Silicone Lubricant
Net Fill	55 Gal
UPC Code	078254032238
Unit Dimensions	35H x 24.5W x 24.5D in
Units Per Case	1
Case Dimensions	35H x 24.5W x 24.5D in
Cases Per Pallet	4
Case Weight	430 lbs
Appearance	Clear Light Yellow Liquid
Base Type	Poly dimthylsiloxane
Flash point (F)	113°F
Flash point (C)	45°C
Flammability Class - CPSC	Combustible
Spec Gravity Concentrate	0.75
Plastic Safe	Safe on Most Plastics (Test small area)
Film Type	Wet
Film Thickness	Not Determined
Evaporation Rate	Slow
Dielectric Strength	Not Determined
Working Temp (F)	-40 to 400°F
Working Temp (C)	-40 to 204.4°C

Last revised: 7/30/2019
Page 1 of 2





Propellant	None
NSF Category Code	H2
NSF Number	139430
DOT Proper Shipping Name	Not Regulated for ground shipping
VOC % (Consumer Product def)	90.4
VOC g/L (Consumer Product def)	684.8
VOC lbs/gal (Consumer Prod def)	5.7
VOC Category	Not Regulated (Single Purpose Lubricant)
Removal (How To)	Remove with Petroleum Distillates.