



## SP-250<sup>™</sup> Corrosion Inhibitor, 5 Gal No. 03226 | Item# 1003468

Product Description Thin, non-staining film protects indoors for up to 9

months. Use for protection of all metals and for parts subjected to high humidity conditions. Perfect as an anti-corrosion coating for shrink-wrapped parts and a moisture

displacer for finished parts.

Applications Machined surfaces, parts in process, power units,

electrical boards, cutting tools, blades, welds, aluminum extrusions, h& tools, dies, molds, chains, guns, artillery &

packaged goods.

Unit Package Description 5 Gallon Pail

Brand CRC

Generic Description 1 Corrosion Inhibitor (Light Duty)

Net Fill 5 Gal

UPC Code 078254032269

Unit Dimensions 13.75H x 11.25W x 11.25D in

Units Per Case 1

Case Dimensions 13.8H x 11.3W x 11.3D in

Cases Per Pallet 24
Case Weight 35 lbs

Appearance Amber Liquid

Flash point (F) 172°F Flash point (C) 78°C

Flammability Class - CPSC Combustible

Spec Gravity Concentrate 0.8034

Film Type Ultra Thin and Dry
Coverage 3,000 Sq Ft per Gal

Plastic Safe No Propellant None

Military Specification Meets requirements of Mil-PRF-16173E, Grade 3

Number (Corrosion test only)

NSF Category Code H2

Last revised: 1/2/2020

Page 1 of 2







NSF Number 132839

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product

def)

VOC g/L (Consumer

Product def)

VOC lbs/gal (Consumer

Prod def)

VOC Category Not Regulated - (Not for field application)

40.6

326.2

2.7

Removal (How To) Remove with petroleum solvents, Stoddard solvent or

mineral spirits.

Last revised: 1/2/2020

Page 2 of 2

