



SP-250™ Corrosion Inhibitor, 5 Gal
 No. 03226 | Item# 1003468

Product Description	Thin, non-staining film protects indoors for up to 9 months. Use for protection of all metals and for parts subjected to high humidity conditions. Perfect as an anti-corrosion coating for shrink-wrapped parts and a moisture displacer for finished parts.
Applications	Machined surfaces, parts in process, power units, electrical boards, cutting tools, blades, welds, aluminum extrusions, h& tools, dies, molds, chains, guns, artillery & packaged goods.
Unit Package Description	5 Gallon Pail
Brand	CRC
Generic Description 1	Corrosion Inhibitor (Light Duty)
Net Fill	5 Gal
UPC Code	078254032269
Unit Dimensions	13.75H x 11.25W x 11.25D in
Units Per Case	1
Case Dimensions	13.8H x 11.3W x 11.3D in
Cases Per Pallet	24
Case Weight	35 lbs
Appearance	Amber Liquid
Flash point (F)	172°F
Flash point (C)	78°C
Flammability Class - CPSC	Combustible
Spec Gravity Concentrate	0.8034
Film Type	Ultra Thin and Dry
Coverage	3,000 Sq Ft per Gal
Plastic Safe	No
Propellant	None
Military Specification Number	Meets requirements of Mil-PRF-16173E, Grade 3 (Corrosion test only)
NSF Category Code	H2

Last revised: 1/2/2020
 Page 1 of 2





NSF Number	132839
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	40.6
VOC g/L (Consumer Product def)	326.2
VOC lbs/gal (Consumer Prod def)	2.7
VOC Category	Not Regulated - (Not for field application)
Removal (How To)	Remove with petroleum solvents, Stoddard solvent or mineral spirits.

Last revised: 1/2/2020
Page 2 of 2