



SP-250[™] Corrosion Inhibitor, 55 Gal No. 03228 | Item# 1003469

Product Description Thin, non-staining film protects indoors for up to 9

months. Use for protection of all metals and for parts subjected to high humidity conditions. Perfect as an anti-corrosion coating for shrink-wrapped parts and a moisture

displacer for finished parts.

Applications Machined surfaces, parts in process, power units,

electrical boards, cutting tools, blades, welds, aluminum extrusions, h& tools, dies, molds, chains, guns, artillery &

packaged goods.

Unit Package Description 55 Gallon Drum

Brand CRC

Generic Description 1 Corrosion Inhibitor (Light Duty)

Net Fill 55 Gal

UPC Code 078254032283

Unit Dimensions 35H x 24.5W x 24.5D in

Units Per Case 1

Case Dimensions 35H x 24.5W x 24.5D in

Cases Per Pallet 4

Case Weight 430 lbs

Appearance Amber Liquid

Flash point (F) 172°F Flash point (C) 78°C

Flammability Class - CPSC Combustible

Spec Gravity Concentrate 0.8034

Film Type Ultra Thin and Dry
Coverage 3,000 Sq Ft per Gal

Plastic Safe No Propellant None

Military Specification Meets requirements of Mil-PRF-16173E, Grade 3

Number (Corrosion test only)

NSF Category Code H2

Last revised: 1/2/2020

Page 1 of 2







NSF Number 132839

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product 45.1

def)

VOC g/L (Consumer 360.8

Product def)

VOC lbs/gal (Consumer 3

Prod def)

VOC Category Not Regulated - (Not for field application)

Removal (How To) Remove with petroleum solvents, Stoddard solvent or

mineral spirits.

