



SP-250™ Corrosion Inhibitor, 55 Gal
 No. 03228 | Item# 1003469

Product Description	Thin, non-staining film protects indoors for up to 9 months. Use for protection of all metals and for parts subjected to high humidity conditions. Perfect as an anti-corrosion coating for shrink-wrapped parts and a moisture displacer for finished parts.
Applications	Machined surfaces, parts in process, power units, electrical boards, cutting tools, blades, welds, aluminum extrusions, h& tools, dies, molds, chains, guns, artillery & packaged goods.
Unit Package Description	55 Gallon Drum
Brand	CRC
Generic Description 1	Corrosion Inhibitor (Light Duty)
Net Fill	55 Gal
UPC Code	078254032283
Unit Dimensions	35H x 24.5W x 24.5D in
Units Per Case	1
Case Dimensions	35H x 24.5W x 24.5D in
Cases Per Pallet	4
Case Weight	430 lbs
Appearance	Amber Liquid
Flash point (F)	172°F
Flash point (C)	78°C
Flammability Class - CPSC	Combustible
Spec Gravity Concentrate	0.8034
Film Type	Ultra Thin and Dry
Coverage	3,000 Sq Ft per Gal
Plastic Safe	No
Propellant	None
Military Specification Number	Meets requirements of Mil-PRF-16173E, Grade 3 (Corrosion test only)
NSF Category Code	H2

Last revised: 1/2/2020
 Page 1 of 2





NSF Number	132839
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	45.1
VOC g/L (Consumer Product def)	360.8
VOC lbs/gal (Consumer Prod def)	3
VOC Category	Not Regulated - (Not for field application)
Removal (How To)	Remove with petroleum solvents, Stoddard solvent or mineral spirits.

Last revised: 1/2/2020
Page 2 of 2