



Oilfield Dry Moly Lube, 11 Wt Oz
 No. 03284 | Item# 1003484 | Case# 1003483

Product Description	Fast drying film resists dirt and dust build-up. Good adhesion and long lasting formula. Lowers friction, prevents galling and helps to reduce torque and energy consumption. High anti-friction and anti-seize properties.
Applications	Use as a surface spray to reduce torque on assemblies. Dries quickly to leave behind moly particles to aid in the assembly or disassembly of dissimilar materials.
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	Dry Film Lubricant
Net Fill	11 Wt Oz
UPC Code	078254032849
Unit Dimensions	7.75H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	8.6H x 8.4W x 11.3D in
Cases Per Pallet	133
Case Weight	12 lbs
I 2 of 5 Code	30078254032840
Appearance	Gray Liquid
Base Type	Molybdenum Disulfide
Flash point (F)	<0°F
Flash point (C)	<-18°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.773
Plastic Safe	No
Film Type	Dry
Evaporation Rate	Fast
Working Temp (F)	650°F (Continuous) / 750°F (Intermittent)
Working Temp (C)	343.3°C (Continuous) 398.9°C (Intermittent)
Propellant	Hydrocarbon

Last revised: 9/5/2019
 Page 1 of 2



Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	66.3
VOC g/L (Consumer Product def)	510.5
VOC lbs/gal (Consumer Prod def)	4.3
VOC Category	Dry Film Lubricant
Removal (How To)	Remove with a heavy duty degreaser.