

Food Grade Synthetic Hydraulic Oil ISO 68, 5 Gal (Discontinued)

No. 04216 | Item# 1003535

Product Description Fully synthetic fluid blended from premium polyalphaolefin

(PAO) base oils with superior additives that meet the requirements for demanding industrial hydraulic systems

within the food industry.

Product Discontinued

Applications

Great for use in all types of food processing facilities. Hydraulic Systems, vacuum pumps, canning, bearings,

valves, circulating oil.

Unit Package Description 5 Gallon Pail

Brand CRC

Generic Description 1 Hydraulic Oil

Net Fill 5 Gal

UPC Code 078254042169

Unit Dimensions 15H x 12W x 12D in

Units Per Case 1

Case Dimensions 15H x 12W x 12D in

Cases Per Pallet 36

Case Weight 38 lbs

Appearance Clear Liquid

Flash point (F) 500°F Flash point (C) 260°C

Flammability Class - CPSC Combustible

Spec Gravity Concentrate 0.84

Plastic Safe Safe on Most Plastics (Test small area)

Evaporation Rate Slow I SO Viscosity Grade 68 SAE Grade 20

Working Temp (F) -50 to 450°F

Working Temp (C) -45.6 to 232.2°C

NSF Category Code H1

Last revised: 2/25/2020

Page 1 of 2





NSF Number 144418

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product 0

def)

Product

Discontinued

VOC g/L (Consumer 0

Product def)

VOC lbs/gal (Consumer 0

Prod def)

VOC Category Not Regulated

Removal (How To) Remove with Petroleum Distillates.

Last revised: 2/25/2020

Page 2 of 2

