

Food Grade Synthetic Hydraulic Oil ISO 68, 55 Gal (Discontinued)

No. 04217 | Item# 1003536

Product Description Fully synthetic fluid blended from premium polyalphaolefin

(PAO) base oils with superior additives that meet the requirements for demanding industrial hydraulic systems

within the food industry.

Product Discontinued

Applications

Great for use in all types of food processing facilities. Hydraulic Systems, vacuum pumps, canning, bearings,

valves, circulating oil.

Unit Package Description 55 Gallon Drum

Brand CRC

Generic Description 1 Hydraulic Oil

Net Fill 55 Gal

UPC Code 078254042176

Unit Dimensions 34.5H x 23W x 23D in

Units Per Case 1

Case Dimensions 34.5H x 23W x 23D in

Cases Per Pallet 4

Case Weight 425 lbs

Appearance Clear Liquid

Flash point (F) 500°F Flash point (C) 260°C

Flammability Class - CPSC Combustible

Spec Gravity Concentrate 0.84

Plastic Safe Safe on Most Plastics (Test small area)

Evaporation Rate Slow
I SO Viscosity Grade 68
SAE Grade 20

Working Temp (F) -50 to 450°F

Working Temp (C) -45.6 to 232.2°C

NSF Category Code H1

Last revised: 2/25/2020

Page 1 of 2





NSF Number 144418

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product 0

def)

Product

Discontinued

VOC g/L (Consumer 0

Product def)

VOC lbs/gal (Consumer 0

Prod def)

VOC Category Not Regulated

Removal (How To) Remove with Petroleum Distillates.

Last revised: 2/25/2020

Page 2 of 2

