



## Premium Garage Door Lube, 10 Wt Oz No. 05032 | Item# 1003651 | Case# 1003650

Product Description A superior PTFE and silicone fortified lubricant that

prevents friction, wear and corrosion, and drives out moisture. Its unique viscosity covers more surface area while penetrating deep into all metal components found on roll-up and overhead doors for maximum protection.

Applications Recommended for use on all garage doors, roll-up and

overhead door assemblies including dock doors, trailer doors as well as side panel doors on beverage trucks. Use to lubricate and protect door hinges, pins, cable, chains,

bearings, rollers, and tracks.

Unit Package Description 16 Ounce Aerosol

Brand CRC

Generic Description 1 Formulated with PTFE and silicone for long-lasting,

outstanding performance

Net Fill 10 Wt Oz

UPC Code 078254050324

Unit Dimensions 7.75H x 2.63W x 2.63D in

Units Per Case 12

Case Dimensions 8.1H x 8.3W x 11.1D in

Cases Per Pallet 133
Case Weight 11 lbs

1 2 of 5 Code 30078254050325

Appearance Light Amber Cloudy Liquid

Base Type Petroleum
Flash point (F) 200°F
Flash point (C) 93.3°C
Flammability Class - CPSC None
Spec Gravity Concentrate 0.82

Plastic Safe Safe on Most Plastics (Test small area)

Film Type Non-Drying
Film Thickness Not Determined

Last revised: 10/3/2018

Page 1 of 2







Evaporation Rate Slow

Dielectric Strength Not Determined
Propellant Carbon Dioxide

Aerosol Flammability Level III

DOT Proper Shipping Name Aerosols, Flammable, Limited Quantity

VOC % (Consumer Product 0

def)

VOC g/L (Consumer 0

Product def)

VOC lbs/gal (Consumer 0

Prod def)

VOC Category Multi-Purpose Lubricant

Removal (How To) Remove with mineral spirits.

Last revised: 10/3/2018

Page 2 of 2

