



## Heavy Duty Silicone Lubricant, 7.5 Wt Oz

No. 05074 | Item# 1003684 | Case# 1003683

Product Description	Lubricates and eliminates squeaking and binding caused by friction. Film is clean and highly resistant to water. Use on nylon, rubber, metal & non-metal surfaces.
Applications	Wood, metal and rubber surfaces. Use in moist and harsh environments. Not for use as an appearance cleaner or on paint.
Unit Package Description	12 Ounce Aerosol
Brand	CRC
Generic Description 1	Multi-Purpose Silicone Lubricant
Net Fill	7.5 Wt Oz
UPC Code	078254050744
Unit Dimensions	6.25H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	6.70H x 11.10W x 8.30D in
Cases Per Pallet	171
Case Weight	8 lbs
I 2 of 5 Code	30078254050745
Appearance	Clear Colorless Liquid
Base Type	Silicone
Flash point (F)	<0°F
Flash point (C)	<-18°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.748
Plastic Safe	No
Film Type	Thin, Dry
Film Thickness	Non-Drying
Evaporation Rate	Fast
Dielectric Strength	350 Volts/Mil
Working Temp (F)	-40 to 400°F

Last revised: 3/26/2019

Page 1 of 2



**Chemical Solutions to Keep You Moving™**

f t+ in • 800-272-8963 • [crcindustries.com](http://crcindustries.com)

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



Working Temp (C)	-40 to 204.4°C
Propellant	Hydrocarbon
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	59.5
VOC g/L (Consumer Product def)	445.1
VOC lbs/gal (Consumer Prod def)	3.7
VOC Category	Silicone Based Multi-Purpose Lubricant
Removal (How To)	Remove with soap & water, CRC HydroForce® All Purpose, etc. and elbow power (scrubbing).