

Bulb & Connector Dielectric Grease, 0.28 Wt Oz No. 05107 | Item# 1003724 | Case# 1003723

Product Description A unique, non-curing compound used for sealing,

protecting & electrical insulating. Improves electrical performance by reducing arcing, voltage drop & other conditions. Also ideal for lubrication plastic & rubber.

Applications Electrical connections, circuit breakers, contacts, spark

plug boots, trailer connectors, HEI distributor, battery terminals, contacts, lubrication of plastic, rubber parts &

o-rings

Unit Package Description 0.28 Ounce Tube

Brand CRC

Generic Description 1 Bulb & Connector Dielectric Grease

Net Fill 0.28 Wt Oz

UPC Code 078254051079

Unit Dimensions 6.25H x 4.5W x .75D in

Units Per Case 12

Case Dimensions 4.87H x 5.18W x 6.43D in

Cases Per Pallet 294
Case Weight 2 lbs

I 2 of 5 Code 30078254051070 Appearance Opaque White Gel

Base Type Silicone
Flash point (F) >500°F
Flash point (C) >260°C
Flammability Class - CPSC None
Spec Gravity Concentrate 1.01

Plastic Safe Safe on Most Plastics (Test small area)

Evaporation Rate <0.01 (Butyl Acetate=1)


Dielectric Strength 500 Volts/Mil
Working Temp (F) -70 to 400°F
Working Temp (C) -56.7 to 204.4°C

Last revised: 1/16/2019

Page 1 of 2







Drop Point None
Propellant None

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product

def)

VOC g/L (Consumer 0 Product def)

VOC lbs/gal (Consumer 0 Prod def)

VOC Category Not Regulated

Removal (How To) Remove with petroleum distillates and chlorinated

solvents.

0

Last revised: 1/16/2019

Page 2 of 2

