



Silaramic® Brake System Grease, 5 Wt Oz
 No. 05361 | Item# 1003793 | Case# 1003792

Product Description	A synthetic, dry-film, ceramic lubricant formulated to reduce brake noise and vibrations by dampening all brake vibrating frequencies. Will not run off or wash out. Works in extreme temp ranges from -50 to 3000°F. Protects against uneven pad wear.
Applications	All brake systems and brake components, including calipers, bushings, holes, pins, inserts, anchors, bolts, calipers and boots
Unit Package Description	5 Ounce Tube
Brand	CRC
Generic Description 1	Brake System Grease
Net Fill	5 Wt Oz
UPC Code	078254053615
Unit Dimensions	6.25H x 2W x 2D in
Units Per Case	12
Case Dimensions	8H x 6.38W x 7.63D in
Cases Per Pallet	175
Case Weight	5 lbs
I 2 of 5 Code	30078254053616
Appearance	Off White Semi Solid Grease
Base Type	Polydimethylsiloxane
Flash point (F)	550°F
Flash point (C)	288°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	1.0
NLGI Grade	2
Timken OK Load Lbs.	Not Determined
Plastic Safe	Yes
Evaporation Rate	Very Slow
Dielectric Strength	Not Determined

Last revised: 1/16/2019
 Page 1 of 2





Working Temp (F)	-50 to 3000°F
Working Temp (C)	-45.6 to 1648.89°C
4 Ball EP	Not Determined
4 Ball Wear	Not Determined
Drop Point	None
Elastomer Compatibility	Compatible
Leakage	0.2
Low Temp Torque	Not Determined
Oil Separation	0.2
Oxidation Stability	-20°F
Pour Point (F)	Not Determined
Water Washout	0.25
Worked Penetration	265 to 295
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Not Regulated
Removal (How To)	Remove with petroleum solvents.

Last revised: 1/16/2019
Page 2 of 2