



Silaramic® Brake System Grease, 5 Wt Oz No. 05361 | Item# 1003793 | Case# 1003792

Product Description A synthetic, dry-film, ceramic lubricant formulated to

reduce brake noise and vibrations by dampening all brake vibrating frequencies. Will not run off or wash out. Works in extreme temp ranges from -50 to 3000°F. Protects

against uneven pad wear.

Applications All brake systems and brake components, including

calipers, bushings, holes, pins, inserts, anchors, bolts,

calipers and boots

Unit Package Description 5 Ounce Tube

Brand CRC

Generic Description 1 Brake System Grease

Net Fill 5 Wt Oz

UPC Code 078254053615

Unit Dimensions 6.25H x 2W x 2D in

Units Per Case 12

Case Dimensions 8H x 6.38W x 7.63D in

Cases Per Pallet 175
Case Weight 5 lbs

I 2 of 5 Code 30078254053616

Appearance Off White Semi Solid Grease

Base Type Polydimethylsiloxane

Flash point (F) 550°F
Flash point (C) 288°C
Flammability Class - CPSC None
Spec Gravity Concentrate 1.0
NLGI Grade 2

Timken OK Load Lbs. Not Determined

Plastic Safe Yes

Evaporation Rate Very Slow

Dielectric Strength Not Determined

Last revised: 1/16/2019

Page 1 of 2







Working Temp (F) -50 to 3000°F

Working Temp (C) -45.6 to 1648.89°C

4 Ball EP Not Determined
4 Ball Wear Not Determined

Drop Point None

Elastomer Compatibility Compatible

Leakage 0.2

Low Temp Torque Not Determined

Oil Separation 0.2
Oxidation Stability -20°F

Pour Point (F) Not Determined

Water Washout 0.25

Worked Penetration 265 to 295

Propellant None

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product 0

def)

VOC g/L (Consumer 0

Product def)

VOC lbs/gal (Consumer 0

Prod def)

VOC Category Not Regulated

Removal (How To) Remove with petroleum solvents.

Last revised: 1/16/2019

Page 2 of 2

