



Silaramic® Brake System Grease, 9 Wt Oz

No. 05363 | Item# 1003796 | Case# 1003795

Product Description A synthetic, dry-film, ceramic lubricant formulated to

reduce brake noise and vibrations by dampening all brake vibrating frequencies. Will not run off or wash out. Works in extreme temp ranges from -50 to 3000°F. Protects

against uneven pad wear.

Applications All brake systems and brake components, including

calipers, bushings, holes, pins, inserts, anchors, bolts,

calipers and boots

Unit Package Description 9 Ounce Tub with Brush

Brand CRC

Generic Description 1 Brake System Grease

Net Fill 9 Wt Oz

UPC Code 078254053639

Unit Dimensions 4.25H x 3.88W x 3.88D in

Units Per Case 12

Case Dimensions 5H x 12.25W x 16D in

Cases Per Pallet 175
Case Weight 8 lbs

1 2 of 5 Code 30078254053630

Appearance Off White Semi Solid Grease

Base Type Polydimethylsiloxane

Flash point (F) 550°F
Flash point (C) 288°C
Flammability Class - CPSC None
Spec Gravity Concentrate 1.1
NLGI Grade 2

Timken OK Load Lbs. Not Determined

Plastic Safe Yes

Evaporation Rate Very Slow

Dielectric Strength Not Determined

Last revised: 11/23/2020

Page 1 of 2







Working Temp (F) -50 to 3000°F
Working Temp (C) -45.6 to 1649°C
4 Ball EP Not Determined
4 Ball Wear Not Determined

Drop Point None

Elastomer Compatibility Compatible

Leakage Not Determined
Low Temp Torque Not Determined

Oil Separation 0.2

Oxidation Stability

Pour Point (F)

Pour Point (C)

Not Determined

Not Determined

Water Washout 0.25

Worked Penetration 265 to 295

Propellant None

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product)

def)

VOC g/L (Consumer 0

Product def)

VOC lbs/gal (Consumer 0

Prod def)

VOC Category Not Regulated

Restricted from Sale In: No State Restrictions

Removal (How To) Remove with brake parts cleaner

Last revised: 11/23/2020

Page 2 of 2

