



Diesel Cold Flow™ Anti-Gel with Lubricity, 30 Fl Oz No. 05632 | Item# 1003834 | Case# 1003833

Product Description A highly concentrated formula that inhibits gelling &

improves flowability of diesel fuel in cold weather. Lowers the pour point by as much as 40 F. when used in the

proper ratios.

Applications For use in diesel engines.

Unit Package Description 1 Quart Can

Generic Description 1 Premium Anti Gel with Lubricity

Brand CRC

Net Fill 30 Fl Oz

UPC Code 078254056326

Unit Dimensions 9.5H x 4.5W x 2.6D in

Units Per Case 12

Case Dimensions 16.3H x 9W x 9.4D in

Cases Per Pallet 50
Case Weight 23 lbs

I 2 of 5 Code 30078254056327 Appearance Light Amber Liquid

Flash point (F) 93.2°F

Flash point (C) 34°C

Flammability Class - CPSC Flammable

Spec Gravity Concentrate 0.88

Plastic Safe No

DOT Proper Shipping Name Flammable Liquids, N.O.S. (Xylene, petroleum naptha)

VOC % (Consumer Product 94.6

def)

VOC g/L (Consumer 829

Product def)

VOC lbs/gal (Consumer 6.92

Prod def)

VOC Category Not Regulated

Last revised: 11/23/2020

Page 1 of 2







Restricted from Sale In: No State Restrictions

Removal (How To) Remove with Petroleum Distillates.

Treatment Ratio Preventative Maintenance: 1 Qt treats 500 Gal,Pre-

existing Condition: 1 Qt treats 125 Gal

Last revised: 11/23/2020

Page 2 of 2

