



## Diesel Cold Flow™ Anti-Gel with Lubricity, 55 Gal No. 05655 | Item# 1003839

Product Description A highly concentrated formula that inhibits gelling &

improves flowability of diesel fuel in cold weather. Lowers the pour point by as much as 40 F. when used in the

proper ratios.

Applications For use in diesel engines.

Unit Package Description 55 Gallon Drum

Generic Description 1 Premium Anti Gel with Lubricity

Brand CRC
Net Fill 55 Gal

UPC Code 078254056555

Unit Dimensions 35H x 24.5W x 24.5D in

Units Per Case 1

Case Dimensions 35H x 24.5W x 24.5D in

Cases Per Pallet 4

Case Weight 441 lbs

Appearance Light Amber Liquid

Flash point (F) 87°F Flash point (C) 30°C

Flammability Class - CPSC Flammable

Spec Gravity Concentrate 0.88
Plastic Safe No

DOT Proper Shipping Name Flammable Liquids, N.O.S. (Xylene, Petroleum Naphtha)

VOC % (Consumer Product

def)

VOC g/L (Consumer

Product def)

829

VOC lbs/gal (Consumer

Prod def)

6.92

94.6

VOC Category Not Regulated

Removal (How To) Remove with Petroleum Distillates.

Last revised: 1/8/2020

Page 1 of 2







Treatment Ratio

Preventative Maintenance: 55 Gal treats 55000 Gal, Preexisting Condition: 55 Gal treats 27500 Gal

Last revised: 1/8/2020

Page 2 of 2

