

## PRODUCT DATA SHEET

Diesel Cold Flow™ Anti-Gel with Lubricity, 55 Gal No. 05655 | Item# 1003839

**Product Description** 

A highly concentrated formula that inhibits gelling & improves flowability of diesel fuel in cold weather. Lowers the pour point by as much as 40 F. when used in the

proper ratios.

**Applications** 

For use in diesel engines.

Unit Package Description

55 Gallon Drum

Generic Description 1

Premium Anti Gel with Lubricity

**CRC** Brand

Net Fill

55 Gal

**UPC** Code

078254056555

**Unit Dimensions** 

35H x 24.5W x 24.5D in

Units Per Case

Case Dimensions

35H x 24.5W x 24.5D in

Cases Per Pallet

Case Weight

441 lbs

**Appearance** 

Amber Liquid

Flash point (F)

87°F

Flash point (C)

30°C

Flammability Class - CPSC

Flammable

Spec Gravity Concentrate

0.88

Plastic Safe

No

**DOT Proper Shipping Name** 

Flammable Liquids, N.O.S. (Xylene, Petroleum Naphtha)

VOC % (Consumer Product

def)

95.4

VOC g/L (Consumer

838.7

Product def)

VOC lbs/gal (Consumer

7.0

Prod def)

**VOC Category** 

Not Regulated

Removal (How To)

Remove with Petroleum Distillates.

Last revised: 9/21/2018

Page 1 of 2



Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



## **PRODUCT DATA SHEET**

Treatment Ratio

Preventative Maintenance: 55 Gal treats 55000 Gal, Preexisting Condition: 55 Gal treats 27500 Gal



Last revised: 9/21/2018

Page 2 of 2

