



Marine Instant Galvanize, 13 Wt Oz No. 06054 | Item# 1003898 | Case# 1003897

Product Description High performance coating of >93% pure zinc that

electrochemically bonds to ferrous metals. Provides protection of hot dip galvanize with on the job

convenience.

Applications Threads, exposed edges, fasteners, conduit, strapping,

welds, fencing, railings, grates, electrical poles, breaker panel housings, rain spouts, signs, doors, trailers, waste

containers, catwalks, and guard rails.

Unit Package Description 16 Ounce Aerosol

Brand CRC

Generic Description 1 Marine Instant Galvanize

Net Fill 13 Wt Oz

UPC Code 078254060545

Unit Dimensions 7.75H x 2.63W x 2.63D in

Units Per Case 12

Case Dimensions 8.68H x 8.43W x 11.31D in

Cases Per Pallet 75
Case Weight 15 lbs

I 2 of 5 Code 30078254060546

Appearance Gray Viscous Liquid

Base Type Modified Epoxy

Flash point (F) -2.2° F Flash point (C) -19° C

Flammability Class - CPSC Extremely Flammable

Spec Gravity Concentrate 0.77 to 0.85

Plastic Safe Yes
Evaporation Rate Fast

Working Temp (F) 130°F (Continuous) 150°F (Intermittent)
Working Temp (C) 54.4°C (Continuous) 65.6°C (Intermittent)

Propellant Hydrocarbon

Last revised: 7/23/2019

Page 1 of 2







Aerosol Flammability Level III

DOT Proper Shipping Name Aerosols, Flammable, Limited Quantity

VOC % (Consumer Product 45.6

def)

VOC g/L (Consumer 555.6

Product def)

VOC lbs/gal (Consumer 4.64

Prod def)

VOC Category Aerosol Coating: Metallic

Removal (How To) Remove with aromatic solvents, Xylene. Toluene can be

used, but is not recommended.

Last revised: 7/23/2019

Page 2 of 2

