



Marine Premium Dielectric Grease, 3.3 Wt Oz No. 06113 | Item# 1003915 | Case# 1003914

Product Description Best New Packaging in the performance category at the

2015 AAPEX/SEMA Show! Simply turn the dial on the Select-A-Bead™ actuator to select the best bead width for your project. A unique, non-curing compound used for sealing, protecting & electrical insulating. Improves electrical performance by reducing arcing & voltage drop. Also ideal for lubricating plastic & rubber. Improves electrical performance in adverse weather conditions. Patented finger-actuated delivery system for smooth,

continuous coverage.

Applications Electrical Connectors and Contacts, Light Bulbs & Sockets,

> Breakers, Electrical Panels, Shore Power Inlets, Trailer Connectors, Bulkhead Connectors, Battery Terminals,

Spark Plugs

Unit Package Description 6 Ounce Pressurized Can

Brand CRC

Generic Description 1 Premium Dielectric Grease

Net Fill 3.3 Wt Oz

UPC Code 078254061139

Unit Dimensions 8.75H x 2W x 2D in

Units Per Case 12

9.4H x 8W x 7.9D in Case Dimensions

Cases Per Pallet 120 Case Weight 6 lbs

I 2 of 5 Code 30078254061130 **Appearance** Opaque White Gel

Base Type Silicone Flash point (F) >572°F >300°C Flash point (C) Flammability Class - CPSC None

Spec Gravity Concentrate

0.97 Plastic Safe Safe on Most Plastics (Test small area)

Last revised: 1/24/2019

Page 1 of 2







Dielectric Strength >450 Volts/Mil
Working Temp (F) -70 to 400°F
Working Temp (C) -56.7 to 204.4°C

Propellant Nitrogen

Aerosol Flammability Level I

DOT Proper Shipping Name Aerosols, Non-Flammable, Limited Quantity

VOC % (Consumer Product <1

def)

VOC g/L (Consumer < 0.01

Product def)

VOC lbs/gal (Consumer < 0.1

Prod def)

VOC Category Not Regulated

Removal (How To) Remove with petroleum distillates and chlorinated

solvents.

Last revised: 1/24/2019

Page 2 of 2

