



Marine Dry Lube with PTFE Technology, 10 Wt Oz No. 06114 | Item# 1003917 | Case# 1003916

Product Description Micro-thin film penetrates & bonds to aluminum, metals,

wood, rubber, plastic and most surfaces. Reduces friction and drag. Seals out moisture and helps prevent corrosion.

Applications Rigging, mast track, rudders, genoa or traveler T-track,

centerboards, daggerboards, deck hardware, tools,

hinges, zippers, fishing reel components

Unit Package Description 16 Ounce Aerosol

Brand CRC

Generic Description 1 Dry Lube
Net Fill 10 Wt Oz

UPC Code 078254061146

Unit Dimensions 7.75H x 2.63W x 2.63D in

Units Per Case 12

Case Dimensions 8.1H x 8.3W x 11.1D in

Cases Per Pallet 133
Case Weight 11 lbs

I 2 of 5 Code 30078254061147

Appearance Hazy White Suspension in Liquid

Base Type PTFE Flash point (F) $<20^{\circ}F$ Flash point (C) $<-7^{\circ}C$

Flammability Class - CPSC Flammable

Spec Gravity Concentrate 0.73

Plastic Safe Not Determined

Evaporation Rate Fast

Dielectric Strength

Working Temp (F)

Working Temp (C)

Propellant

Not Determined

-40 to 450°F

-40 to 232.2°C

Hydrocarbon

Last revised: 2/18/2021

Page 1 of 2







Aerosol Flammability Level III

DOT Proper Shipping Name Aerosols, Flammable, Limited Quantity

VOC % (Consumer Product 98

def)

VOC g/L (Consumer 715.4

Product def)

VOC lbs/gal (Consumer 5.96

Prod def)

VOC Category Dry Film Lubricant

Removal (How To) Remove with IPA or hexane if wet; hard rubbing when

dry.

Last revised: 2/18/2021

Page 2 of 2

