



**Food Zone Silicone Sealant - Aluminum, 10.1 Fl Oz**  
 No. 14088 | Item# 1004824 | Case# 1004823



Product Description	NSF Certified for Food Zone sealing, bonding, protecting and waterproofing applications. Aluminum formulation is designed for high moisture, indoor/outdoor applications.
Applications	Sealing, bonding, protection & waterproofing in tanks, pipes, electrical, construction, metal working, for filling gaps between mating parts, gearboxes, pumps, motors & for general gasket sealing
Unit Package Description	12 Ounce Cartridge
Brand	CRC
Generic Description 1	Aluminum Silicone Sealant
Net Fill	10.1 Fl Oz
UPC Code	078254140889
Unit Dimensions	8.25H x 1.5W x 1.5D in
Units Per Case	12
Case Dimensions	10H x 6W x 7.75D in
Cases Per Pallet	120
Case Weight	10 lbs
I 2 of 5 Code	30078254140880
Appearance	Aluminum Paste
Flash point (F)	>212°F
Flash point (C)	>100°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	1.01
Plastic Safe	Yes
Evaporation Rate	Slow
Curing Time	24 Hours
Dielectric Strength	25 kV/mm
Working Temp (F)	-70 to 400°F
Working Temp (C)	-57 to 205°C
Propellant	None

Last revised: 10/8/2019  
 Page 1 of 2





DOT Proper Shipping Name	Not Regulated
Military Specification Number	Meets requirements of Mil-A-46106 Type 1
Federal Specification Number	TT-S-001543A Class B, TT-S-0230C Type 2 Class B
VOC % (Consumer Product def)	<3.0
VOC g/L (Consumer Product def)	<31
VOC lbs/gal (Consumer Prod def)	<0.26
VOC Category	Sealant or Caulking Compound, chemically curing, nonaerosol
Removal (How To)	Scraping or a gasket remover product