



Perma-Mend™ UV Curable Repair Patch

No. 14096 | Item# 1004832 | Case# 1004831

Product Description Light activated fiberglass reinforced self adhesive repair

patch.

Applications Repair of tanks, pipes, roofs, steps, switch boxes,

radiators, mufflers, bumpers, boat bodies. Can be used on any wood, metal, glass, ceramic, concrete and plastic

surface.

Unit Package Description 9" x 12" Patch

Brand CRC

Generic Description 1 Repair Patch

Net Fill 9" x 12"

UPC Code 078254140964

Unit Dimensions 9H x 12W

Units Per Case 12

Case Dimensions 2.25H x 11.5W x 15.75D in

Cases Per Pallet 50

Case Weight 10 lbs

I 2 of 5 Code 30078254140965

Appearance Grey Sheet Lamination

Flash point (F) 840°F
Flash point (C) 449°C
Flammability Class - CPSC None
Spec Gravity Concentrate 0.91
Plastic Safe Yes
Evaporation Rate None

Curing Time 5 Minutes (Sunny),50 Minutes (Cloudy)

Dielectric Strength 9 kV/mm

Working Temp (F) -40 to 392°F

Working Temp (C) -40 to 200°C

DOT Proper Shipping Name Not Regulated

Last revised: 10/8/2019

Page 1 of 2







VOC % (Consumer Product 0.6

def)

VOC g/L (Consumer Product def)

Not Determined

VOC lbs/gal (Consumer

Not Determined

Prod def)

VOC Category Not Regulated

Last revised: 10/8/2019

Page 2 of 2

