



Rust Proof Enamel Spray Paint-OSHA Yellow, 15 Wt Oz

No. 18101 | Item# 1005202 | Case# 1005201

Product Description	Rust resistant, premium quality alkyd enamel. Designed for moderate to severe corrosive environments & is specially formulated to resist rusting, peeling & fading. Fights weathering, salt spray, & the most severe & demanding industrial conditions.
Color	OSHA Yellow
Applications	For use on iron, steel, wood and aluminum
Unit Package Description	20 Ounce Aerosol
Brand	CRC
Generic Description 1	Rust Proof Enamel Spray Paint
Net Fill	15 Wt Oz
UPC Code	078254181011
Unit Dimensions	9.25H x 2.63W x 2.63D in
Units Per Case	6
Case Dimensions	9.75H x 5.5W x 8.5D in
Cases Per Pallet	152
Case Weight	8 lbs
I 2 of 5 Code	30078254181012
Appearance	Yellow Liquid
Flash point (F)	-2.2°F
Flash point (C)	-19°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.77 to 0.85
Plastic Safe	Yes
Dry Time - Fully Dry	2 Hours
Dry Time - Tack Free	30 Minutes
Recoat	Before 1 Hour or After 48 Hours
Coverage	25 to 40 Sq Ft
Propellant	Hydrocarbon

Last revised: 1/8/2020
Page 1 of 2





Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	45.9
VOC g/L (Consumer Product def)	531
VOC lbs/gal (Consumer Prod def)	4.43
VOC Category	Aerosol Coating: Non-Flat Paint
MIR Limit (EPA)	1.4
MIR Limit (CA)	0.95
MIR Value	0.7
Removal (How To)	Remove: WET paint with mineral spirits or turpentine, DRY paint with lacquer thinner/stripper.

Last revised: 1/8/2020
Page 2 of 2