



## Upside Down Marking Paints-Safety Green, 17 Wt Oz

No. 18203 | Item# 1005222 | Case# 1005221

Product Description	Clearly and effectively marks the location of underground utilities. Colors meet the A.P.W.A. One Call International Color Standards. Safe to use on turf grass, fields, and golf courses.
Color	Safety Green
Applications	To identify and code surfaces such as metal, concrete, asphalt, gravel, soil, trees and grass for construction, utility, recreational, municipal and landscaping sites, golf courses, nurseries and surveying.
Unit Package Description	20 Ounce Aerosol
Brand	CRC
Generic Description 1	Upside Down Marking Paints
Net Fill	17 Wt Oz
UPC Code	078254182032
Unit Dimensions	9.25H x 2.63W x 2.63D in
Units Per Case	6
Case Dimensions	10.18H x 5.6W x 11.3D in
Cases Per Pallet	136
Case Weight	8 lbs
1 2 of 5 Code	30078254182033
Appearance	Green Liquid
Flash point (F)	-2°F
Flash point (C)	-19&#176;C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.77 to 0.85
Plastic Safe	Yes
Dry Time - Fully Dry	2 Hours
Dry Time - Tack Free	30 Minutes
Recoat	Before 1 Hour or After 72 Hours
Coverage	0 to 700 Linear Feet

Last revised: 7/23/2019  
Page 1 of 2





Propellant	Hydrocarbon
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	44.8
VOC g/L (Consumer Product def)	535.5
VOC lbs/gal (Consumer Prod def)	4.47
VOC Category	Aerosol Coating: Ground Traffic/Marking
MIR Limit (EPA)	1.2
MIR Limit (CA)	0.85
MIR Value	0.59
Removal (How To)	Remove: WET paint with mineral spirits or turpentine, DRY paint with lacquer thinner/stripper.

Last revised: 7/23/2019  
Page 2 of 2