



## Seal Coat® Clear Urethane Coating, 11 Wt Oz No. 18411 | Item# 1005238 | Case# 1005237

insulates electrical equipment and seals out water and moisture. This product allows clear visualization of whatever it is sprayed upon. It is an excellent insulator of PC boards, since it allows visualization of circuit paths. It

dries quickly to a hard, durable, flexible film.

Color Clea

Applications On motor windings, terminals, bus bars, commutator

ends, stator coils, and PC boards

Unit Package Description 16 Ounce Aerosol

Brand CRC

Generic Description 1 Urethane Coating

Net Fill 11 Wt Oz

UPC Code 078254184111

Unit Dimensions 7.75H x 2.63W x 2.63D in

Units Per Case 12

Case Dimensions 8.6H x 8.4W x 11.3D in

Cases Per Pallet 133
Case Weight 11 lbs

I 2 of 5 Code 30078254184112

Appearance Clear Viscous Liquid

Flash point (F)  $-4^{\circ}F$ Flash point (C)  $-20^{\circ}C$ 

Flammability Class - CPSC Extremely Flammable

Spec Gravity Concentrate 0.717
Plastic Safe Yes

Evaporation Rate Moderate
Dry Time - Fully Dry 72 Hours

Dry Time - Tack Free 15 to 30 Minutes Coverage 20 to 25 Sq Ft

Last revised: 4/30/2020

Page 1 of 2







Dielectric Strength 3,000 Volts/Mil
Working Temp (F) -90 to 250°F
Working Temp (C) -67.8 to 121.1°C

Aerosol Flammability Level III

DOT Proper Shipping Name Aerosols, Flammable, Limited Quantity

Hydrocarbon

VOC % (Consumer Product 63.9

def)

VOC g/L (Consumer 457.8

Product def)

Propellant

VOC lbs/gal (Consumer 3.8

Prod def)

VOC Category Aerosol Coating: Electrical Coating

MIR Limit (EPA) None
MIR Limit (CA) 2.0
MIR Value 1.46

Removal (How To) Extremely difficult to remove, scraping is recommended.

Last revised: 4/30/2020

Page 2 of 2

